

100 and a wireless power receiver 200 that can be employed in the embodiments disclosed herein.

[0074] Wireless Power Transmitter

[0075] Referring to FIG. 2A, the wireless power transmitter 100 may include a power transmission unit 110. The power transmission unit 110 may include a power conversion unit 111 and a power transmission control unit 112.

[0076] The power conversion unit 111 transfers power supplied from a transmission side power supply unit 190 to the wireless power receiver 200 by converting it into a wireless power signal. The wireless power signal transferred by the power conversion unit 111 is generated in the form of a magnetic field or electro-magnetic field having an oscillation characteristic. For this purpose, the power conversion unit 111 may be configured to include a coil for generating the wireless power signal.

[0077] The power conversion unit 111 may include a constituent element for generating a different type of wireless power signal according to each power transfer method. For example, the power conversion unit 111 may include a primary coil for forming a changing magnetic field to induce a current to a secondary coil of the wireless power receiver 200. Furthermore, the power conversion unit 111 may include a coil (or antenna) for forming a magnetic field having a specific resonant frequency to generate a resonant frequency in the wireless power receiver 200 according to the resonance coupling method.

[0078] Furthermore, the power conversion unit 111 may transfer power using at least one of the foregoing inductive coupling method and the resonance coupling method.

[0079] Among the constituent elements included in the power conversion unit 111, those for the inductive coupling method will be described later with reference to FIGS. 4 and 5, and those for the resonance coupling method will be described with reference to FIGS. 7 and 8.

[0080] On the other hand, the power conversion unit 111 may further include a circuit for controlling the characteristics of a used frequency, an applied voltage, an applied current or the like to form the wireless power signal.

[0081] The power transmission control unit 112 controls each of the constituent elements included in the power transmission unit 110. The power transmission control unit 112 may be implemented to be integrated into another control unit (not shown) for controlling the wireless power transmitter 100.

[0082] On the other hand, a region to which the wireless power signal can be approached may be divided into two types. First, an active area denotes a region through which a wireless power signal transferring power to the wireless power receiver 200 is passed. Next, a semi-active area denotes an interest region in which the wireless power transmitter 100 can detect the existence of the wireless power receiver 200. Here, the power transmission control unit 112 may detect whether the wireless power receiver 200 is placed in the active area or detection area or removed from the area. Specifically, the power transmission control unit 112 may detect whether or not the wireless power receiver 200 is placed in the active area or detection area using a wireless power signal formed from the power conversion unit 111 or a sensor separately provided therein. For instance, the power transmission control unit 112 may detect the presence of the wireless power receiver 200 by monitoring whether or not the characteristic of power for forming the wireless power signal is changed by the wireless power

signal, which is affected by the wireless power receiver 200 existing in the detection area. However, the active area and detection area may vary according to the wireless power transfer method such as an inductive coupling method, a resonance coupling method, and the like.

[0083] The power transmission control unit 112 may perform the process of identifying the wireless power receiver 200 or determine whether to start wireless power transfer according to a result of detecting the existence of the wireless power receiver 200.

[0084] Furthermore, the power transmission control unit 112 may determine at least one characteristic of a frequency, a voltage, and a current of the power conversion unit 111 for forming the wireless power signal. The determination of the characteristic may be carried out by a condition at the side of the wireless power transmitter 100 or a condition at the side of the wireless power receiver 200.

[0085] The power transmission control unit 112 may receive a power control message from the wireless power receiver 200. The power transmission control unit 112 may determine at least one characteristic of a frequency, a voltage and a current of the power conversion unit 111 based on the received power control message, and additionally perform other control operations based on the power control message.

[0086] For example, the power transmission control unit 112 may determine at least one characteristic of a frequency, a voltage and a current used to form the wireless power signal according to the power control message including at least one of rectified power amount information, charging state information and identification information in the wireless power receiver 200.

[0087] Furthermore, as another control operation using the power control message, the wireless power transmitter 100 may perform a typical control operation associated with wireless power transfer based on the power control message. For example, the wireless power transmitter 100 may receive information associated with the wireless power receiver 200 to be auditorily or visually outputted through the power control message, or receive information required for authentication between devices.

[0088] In exemplary embodiments, the power transmission control unit 112 may receive the power control message through the wireless power signal. In other exemplary embodiment, the power transmission control unit 112 may receive the power control message through a method for receiving user data.

[0089] In order to receive the foregoing power control message, the wireless power transmitter 100 may further include a modulation/demodulation unit 113 electrically connected to the power conversion unit 111. The modulation/demodulation unit 113 may modulate a wireless power signal that has been modulated by the wireless power receiver 200 and use it to receive the power control message.

[0090] In addition, the power transmission control unit 112 may acquire a power control message by receiving user data including a power control message by a communication means (not shown) included in the wireless power transmitter 100.

[0091] [For Supporting In-Band Two-Way Communication]

[0092] Under a wireless power transfer environment allowing for bi-directional communications according to the exemplary embodiments disclosed herein, the power trans-